

Amplifiers / Subwoofers

Release the Power From Within.



Energize Your Music with Exceptional Performance



XC1410



XC6610



XC6410



XC6210

Feature Comparison

	Maximum Power Output	4-Ohm	2-Ohm	Type	Number of Channels	Dimensions (W" x L" x H")	CEA 2006 Power Ratings
New XC1410	300W	50W x 4	75W x 4	Class D	4	7-1/8 x 2-3/4 x 1-3/8	75W x 4 RMS [2Ω @ ≤ 14.4V 1% THD+N] 50W x 4 RMS [4Ω @ ≤ 14.4V 1% THD+N] S/N 80dB (Ref: 1W into 4Ω)
New XC6610	1000W	85W x 6	125W x 6	Class D	6/5/4/3	11-3/8 x 6-7/8 x 2-3/16	125W x 6 RMS [2Ω @ ≤ 14.4V 1% THD+N] 85W x 6 RMS [4Ω @ ≤ 14.4V 1% THD+N] S/N 80dB (Ref: 1W into 4Ω)
XC6410	600W	85W x 4	125W x 4	Class D	4/3/2	8-3/4 x 6-7/8 x 2-3/16	125W x 4 RMS [2Ω @ ≤ 14.4V 1% THD+N] 85W x 4 RMS [4Ω @ ≤ 14.4V 1% THD+N] S/N 80dB (Ref: 1W into 4Ω)
XC6210	350W	85W x 2	125W x 2	Class D	2/1	6-3/8 x 6-7/8 x 2-3/16	125W x 2 RMS [2Ω @ ≤ 14.4V 1% THD+N] 85W x 2 RMS [4Ω @ ≤ 14.4V 1% THD+N] S/N 80dB (Ref: 1W into 4Ω)
XR2120	570W	280W x 1	400W x 1	Class AB	Mono	14 x 8-1/2 x 2-3/16	280W x 1 RMS [4Ω @ 14.4V ≤ 1% THD+N] S/N 70dB (Ref: 1W into 4Ω)
XR2420	480W	60W x 4	90W x 4	Class AB	4/3/2	14 x 8-1/2 x 2-3/16	60W x 4 RMS [4Ω @ 14.4V ≤ 1% THD+N] S/N 80dB (Ref: 1W into 4Ω)
XR2220	280W	65W x 2	95W x 2	Class AB	2/1	11-5/8 x 8-1/2 x 2-3/16	60W x 2 RMS [4Ω @ 14.4V ≤ 1% THD+N] S/N 85dB (Ref: 1W into 4Ω)



More Gravity for the Bass Line.



Formidable Bass Performance in a Unique Shallow-Mount Design for Flexible Installation

SRV250 **New**

150W Max. Amplified Subwoofer Low-profile Design

- 6-3/4" Subwoofer
- Built-in MOS-FET power amp with 150W max. output
- Low-profile design allows installation under seat
- AMI-PP cone with aramid fiber mixed in polypropylene
- Rigid aluminum die-cast enclosure for tight bass reproduction
- Independent buttons for Gain control/Low-pass filter/Phase shift on Wired Remote Control (cable: 6.5ft)
- RCA/Speaker level inputs
- Remote control extension cable (13ft) included
- Dimension = Main unit : 10-13/16" (w) x 2-3/4" (H) x 7-11/16" (D)
Remote control unit : 1-1/4" (w) x 1" (H) x 4-3/8" (D)
- Weight = Main unit : 5.5 Lbs
Remote control unit : 0.2 Lbs



Power Output:
29 W x 2 RMS [2Ω @ 14.4V ≤ 1% THD+N]
Signal to Noise Ratio:
S/N265dB (Ref: 1W into 2Ω)



Developed Specifically to Deliver Big Bass Sound with a Relatively Small Investment

Feature Comparison

	Size	Maximum Power Handling	High Strength Stamped Steel	Dual Voice Coil	CEA-2031 Speaker Rating
New WF2520D	10"	1000W	●	●	Maximum RMS Power: 300watts Impedance: 4 ohms + 4 ohms
New WF2520	10"	1000W	●	—	Maximum RMS Power: 300watts Impedance: 4 ohms
New WG3020D	12"	1000W	●	●	Maximum RMS Power: 300 watts Impedance: 4 ohms + 4 ohms
New WG3020	12"	1000W	●	—	Maximum RMS Power: 300 watts Impedance: 4 ohms
New WG2520D	10"	1000W	●	●	Maximum RMS Power: 300watts Impedance: 4 ohms + 4 ohms
New WG2520	10"	1000W	●	—	Maximum RMS Power: 300watts Impedance: 4 ohms

Speakers

Technology Resonating with Brilliant Sound.



Multiaxial and Component Speakers Provide A Perfect Solution for Your Acoustic Environment



Feature Comparison

	Size	Maximum Power Handling	Type	CEA-2031 Speaker Rating
SRQ1722S	6-3/4"	400W	2-Way Component System	Maximum RMS Power:55 watts Impedance: 4 ohms
SRQ1622S	6-1/2"	350W	2-Way Component System	Maximum RMS Power:55 watts Impedance: 4 ohms
SRQ6933R	6" x 9"	500W	Multiaxial 3-Way	Maximum RMS Power:80 watts Impedance: 4 ohms
SRQ1732R	6-3/4"	400W	Multiaxial 3-Way	Maximum RMS Power:55 watts Impedance: 4 ohms
SRQ1632R	6-1/2"	350W	Multiaxial 3-Way	Maximum RMS Power:55 watts Impedance: 4 ohms
SRQ6832C	6" x 8"	350W	Custom Fit Multiaxial 3-Way	Maximum RMS Power:55 watts Impedance: 4 ohms
SRQ1332R	5-1/4"	300W	Multiaxial 3-Way	Maximum RMS Power:35 watts Impedance: 4 ohms
SRQ212H	3/4"	250W	Tweeter	Maximum RMS Power:45 watts Impedance: 4 ohms



Full Range of Coaxial Speakers to Easily Upgrade Your Car's Factory System



Feature Comparison

	Size	Maximum Power Handling	Type	CEA-2031 Speaker Rating
SRG6932R	6" x 9"	400W	Multiaxial 3-Way	Maximum RMS Power:50 watts Impedance: 4 ohms
SRG1622R	6-1/2"	250W	Coaxial 2-Way	Maximum RMS Power:35 watts Impedance: 4 ohms
SRG1322R	5-1/4"	230W	Coaxial 2-Way	Maximum RMS Power:30 watts Impedance: 4 ohms
SRG1022R	4"	180W	Coaxial 2-Way	Maximum RMS Power:30 watts Impedance: 4 ohms
SRG6832C	6" x 8"	300W	Custom Fit Multiaxial 3-Way	Maximum RMS Power:45 watts Impedance: 4 ohms
SRG5732C	5" x 7"	250W	Custom Fit Multiaxial 3-Way	Maximum RMS Power:40 watts Impedance: 4 ohms
SRG4622C	4" x 6"	200W	Custom Fit Coaxial 2-Way	Maximum RMS Power:30 watts Impedance: 4 ohms
SRG922C	3-1/2"	80W	Custom Fit Coaxial 2-Way	Maximum RMS Power:20 watts Impedance: 4 ohms



* For functional details please visit the Clarion website.